



SMD SPRING COIL

SMD TYPE

E2 TYPE

DIMENSIONS & SPECIFICATION

UNIT : mm



Ordering code	Wire(φ)	I.D(φ)	Turns	Inductance range (nH)	TAPE
E2-0.15-0.4-3T	0.15	0.4	3T	3.6	-
E2-0.18-0.7-4T	0.18	0.7	4T	9.5	LF
E2-0.18-0.7-5T	0.18	0.7	5T	12.8	LJ
E2-0.20-0.8-4T	0.20	0.8	4T	11.0	A51
E2-0.20-0.8-5T	0.20	0.8	5T	15	LJ
E2-0.25-1.0-5T	0.25	1.0	5T	18.3	4T,5T
E2-0.25-1.8-8T	0.25	1.8	8T	77.4	6T,7T
E2-0.25-1.8-9T	0.25	1.8	9T	91.8	6T,7T
E2-0.26-1.2-3T	0.26	1.2	3T	11.0	A52
E2-0.26-1.2-4T	0.26	1.2	4T	17.4	GH
E2-0.26-1.2-5T	0.26	1.2	5T	22.6	FN(1)
E2-0.28-1.0-4T	0.28	1.0	4T	12.0	HN
E2-0.28-1.0-5T	0.28	1.0	5T	16.0	GH
E2-0.28-1.0-6T	0.28	1.0	6T	21.0	FN(1)
E2-0.28-1.1-6T	0.28	1.1	6T	24	FN(1)
E2-0.30-1.0-3T	0.30	1.0	3T	9.0	GE
E2-0.30-1.0-4T	0.30	1.0	4T	12.0	HN
E2-0.30-1.0-5T	0.30	1.0	5T	15.0	FN(1)
E2-0.32-1.0-3T	0.32	1.0	3T	8.0	GE
E2-0.35-1.4-5T	0.35	1.4	5T	23.0	ELK34(1)
E2-0.35-1.6-4T	0.35	1.6	4T	21.0	4T,5T
E2-0.35-1.6-5T	0.35	1.6	5T	28.0	4T,5T
E2-0.40-1.5-4T	0.40	1.5	4T	19.6	4T,5T
E2-0.40-1.5-5T	0.40	1.5	5T	24.0	6T,7T
E2-0.40-1.5-6T	0.40	1.5	6T	31.0	4T,5T
E2-0.40-3.0-8T	0.40	3.0	8T	128.5	HD
E2-0.40-3.0-9T	0.40	3.0	9T	150.0	HD
E2-0.4-3.0-10T	0.40	3.0	10T	174.0	HE
E2-0.45-1.4-3T	0.45	1.4	3T	11.0	4T,5T
E2-0.45-1.4-4T	0.45	1.4	4T	15.0	6T,7T
E2-0.45-1.5-5T	0.45	1.5	5T	23.2	6T,7T
E2-0.50-2.0-5T	0.50	2.0	5T	34.4	B36
E2-0.50-2.0-6T	0.50	2.0	6T	42.7	B36
E2-0.60-2.6-5T	0.60	2.6	5T	44.8	-
E2-0.80-3.0-6T	0.80	3.0	6T	61.5	-

Standard Parts selection Guide

*TEST Equipments : Agilent 4284A (1MHz 500mV)

LS-Q 1MHz / 500mV

HP16034E TEST FIXTURE

Note: can purchase customizing type, please contact us.